

PROVISION OF TREE PLANTING/MAINTENANCE SERVICES

URGENT

**PLEASE FORWARD THIS DOCUMENT TO
WHOEVER IS IN POSSESSION OF THE BID
OPPORTUNITY**

ISSUED: March 30, 2007
BY: Debbie Shkolny
TELEPHONE NO. (204) 986-2249

**THIS ADDENDUM SHALL BE INCORPORATED
INTO THE BID OPPORTUNITY AND SHALL
FORM A PART OF THE CONTRACT
DOCUMENTS**

Template Version: A20060821

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Bid may render your Bid non-responsive.

PART E – SPECIFICATIONS

Replace: E10.1 with the following:

E10.1 The Contractor is expected to plant trees as follows:

- (a) all trees shall be set plumb and shall be placed in the centre of the tree pit;
- (b) trees shall be placed on undisturbed soil and to a depth equal as stated in E8.2(c);
- (c) once the tree has been set in its final position, burlap on the root ball shall be folded back from the top 1/3 of the root ball:
 - (i) If a wire basket has been used, it shall be cut off from the top 1/3 of the root ball;
 - (ii) All twine shall be removed from the root ball.
- (d) after the root ball is prepared, fill tree pit with planting soil as per E7.3, in layers of 150 mm depth and compact the independent layers of soil by tamping;
- (e) when 2/3 of soil has been placed around tree, fill the tree pit with water;
- (f) allow the water to penetrate into the soil and complete the backfilling of the soil;
- (g) tamp soil around root system to eliminate air voids;
- (h) grade the area around the tree according to the drainage type; and
- (i) all planting areas shall be levelled, raked and edged to give a neat appearance.

DRAWINGS

Replace: 218-2007_Drawing_2-R0.pdf with 218-2007_Addendum_1-Drawing_2-R1.pdf