



702-2009 ADDENDUM 2

NORQUAY COMMUNITY CENTRE PLAYGROUND DEVELOPMENT – SUPPLY AND INSTALLATION OF PLAY EQUIPMENT

URGENT

**PLEASE FORWARD THIS DOCUMENT TO
WHOEVER IS IN POSSESSION OF THE BID
OPPORTUNITY**

ISSUED: September 29, 2009
BY: Jennifer Wagner
TELEPHONE NO. (204) 986-2491

**THIS ADDENDUM SHALL BE INCORPORATED
INTO THE BID OPPORTUNITY AND SHALL
FORM A PART OF THE CONTRACT
DOCUMENTS**

Template Version: A20070419

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Bid may render your Bid non-responsive.

PART A – BID SUBMISSION

Replace: 702-2009 Bid Submission with 702-2009 Addendum 2 - Bid Submission. The following is a summary of changes incorporated in the replacement Bid Submission:

Form B(R1): Revise description of 2. "Swing Standard - -2-Bay, 3.0m (10') Ht., 4 Belt" to read "Swing Standard – 2-Bay, 3.0m (10') Ht., 3 Belt Seats, 1 Infant Seat."

PART E – SPECIFICATIONS

Revise E19.2 to read:

E19.2 Materials

E19.2.1 Colour

(a) The colours of the Swing Standard shall be bright primary for all Poles, Clamps, Components, Accents, etc.

E19.2.2 Topbeam

(a) All topbeams shall be fabricated from 3 1/2" O.D. 7 gauge, RS40 galvanized steel pipe with a baked-on polyester powdercoating or galvanized steel. The powder coating finish shall meet or exceed ASTM standards for hardness, adhesion, impact and salt spray resistance. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating prior to powdercoating.

E19.2.3 Legs

(a) All legs shall be fabricated from 2 3/8" O.D. 10 gauge, RS40 galvanized steel pipe with a baked-on polyester powdercoating or galvanized steel. The powder coating finish shall meet or exceed ASTM standards for hardness, adhesion, impact and salt spray resistance. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating prior to powdercoating. The bottom end of the posts is to be sealed with a moisture barrier.

E19.2.4 Yoke Clamps

(a) All yoke clamps shall be either one piece construction and fabricated from 8 gauge, RS40 galvanized steel pipe or two piece, compression clamping cast aluminum or galvanized metal complete with tamper-proof hardware.

- E19.2.5 Swing Hangers
(a) All swing hangers shall be fabricated from galvanized malleable iron and have oil impregnated bearings pressed in.
- E19.2.6 Swing Chain
(a) All swing chain shall be 4/0 straight link, galvanized steel.
- E19.2.7 Belt Seats
(a) All belt seats shall be moulded of U.V. stabilized, high quality, rubber with a tempered stainless steel reinforcement plate insert moulded inside, rendering the seats slashproof. The perimeter shall be moulded to form a blunt, impact absorbing edge.
- E19.2.8 Enclosed Infant (Bucket) Seats
(a) All enclosed infant seats shall be moulded of U.V. stabilized, high quality, rubber with a tempered stainless steel reinforcement plate insert moulded inside, rendering the seats slashproof. Infant seats shall be fully enclosed to prevent slipping out and provide extra lower back support.
- E19.2.9 Hardware
(a) All fasteners shall be tamper proof in design, requiring special tools. The fasteners shall be either carbon steel plated with zinc/nickel and iridescent chromate finish or stainless steel.
- E19.2.10 Concrete Foundations
(a) Post shall be installed into a concrete footing the composition of which is detailed in E20.

Revise: E21.2.2 to read:

- E21.2.2 Materials
- (a) Wood Fibre product shall be either Zeager Woodcarpet or Fibar FibarSystem 300 products or substitute acceptable to Contract Administrator.
- (i) Contact for Woodcarpet:
Zeagar Bros. Inc.
4000 East Harrisburg Pike ·
Middletown, PA 17057
USA

Ph: (1-888) 346-8524 or (717) 944-7481 ·
Fax (717) 944-7681
sales@zeager.com
- (ii) Contact for FibarSystem 300:
The Fibar Group LLC
80 Business Park Drive, Suite 300
Armonk, NY 10504-1705
USA

Ph: (800) 342-2721
Fax: (914) 273-8659
info@FibarPlaygrounds.com
- (b) Wood Fibre surfacing shall include wood fibre, filter cloth, subsurface drainage system and mats for bottom of slides, if applicable.