

**Part 1            General**

**1.1                PRODUCT DATA**

- .1        Submit manufacturer's printed product literature, specifications, and application instructions to Contract Administrator before commencing application.09 91 23 - Interior Painting

**1.2                ENVIRONMENTAL CONDITIONS**

- .1        Maintain ambient and structural base temperature at installation area within limits specified by coating manufacturer. Apply coating during dry weather. Do not apply coating to wet or damp surfaces.Non-rated hollow steel doors

**1.3                PROTECTION**

- .1        Protect plants and vegetation that might be damaged by coating. Protect surfaces not intended to have application of 1coatings. Provide adequate ventilation or isolation measures to protect against toxic fumes.

**Part 2            Products**

**2.1                MATERIALS**

- .1        Graffiti-resistant coating: one component, water based, non-sacrificial, clear penetrating sealer and liquid repellent.
- .2        Acceptable products: Fabrikem Fabrishield Paint Repellent PR-61 for clay brick.
- .3        Or approved equal in accordance with B8.

**Part 3            Execution**

**3.1                PREPARATION**

- .1        Prepare and clean substrate surfaces in accordance with coating manufacturer's instructions.
- .2        Mix and prepare coatings to manufacturer's instructions.
- .3        Take moisture tests on substrates to receive coating to ensure moisture levels are within limits specified by coating manufacturer.

**3.2                APPLICATION**

- .1        Apply coating using low pressure spraying apparatus, at recommended coverage rate for product and substrate.
  - .2        Apply in uniform, even coat to fully wet substrate, without flooding or rundowns.
  - .3        Allow area to dry completely before applying additional coats.
-

**3.3 SCHEDULE**

- .1 Apply graffiti-resistant coating to clay brick.

**Part 4 Measurement and Payment**

**4.1 METHOD OF MEASUREMENT AND PAYMENT**

- .1 Graffiti-Resistant Coatings

The supply and installation of graffiti-resistant coatings shall be considered incidental to the Contract Lump Sum Price for "Building".

**END OF SECTION**

---