



232-2005 ADDENDUM 1

PLAYGROUND REDEVELOPMENT – BERKSHIRE, PULBERRY & EDGEWOOD PARKS

URGENT

PLEASE FORWARD THIS DOCUMENT TO WHOEVER IS IN POSSESSION OF THE BID OPPORTUNITY

ISSUED: July 5, 2005
BY: Carmen Sorby
TELEPHONE NO. (204) 986-3855

THIS ADDENDUM SHALL BE INCORPORATED INTO THE BID OPPORTUNITY AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS

Template Version: A20050506

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Bid may render your Bid non-responsive.

PART E – SPECIFICATIONS

Revise E2.1.3 to read:

E2.1.3 The specific play equipment is as follows:

Park	Location	Description	Type	Quantity
Berkshire Bay Park	Berkshire Bay, E. of Oakmont Ave.	Play structure	Style 1	one (1) each
		Swing	Type 2	one (1) each
		Spring Rider	Style B	one (1) each
Edgewood Park	Beaverhill Blvd betw. Park Grove & Lake Lawn Drives	Play structure	Style 3	one (1) each
		Spring rider	Style A	one (1) each
		Spring See Saw		one (1) each
Pulberry Park	W. of Cabot Cr. N. of Triton Bay	Play structure	Style 2	one (1) each

Add E2.1.4 as follows:

E2.1.4 Colour Scheme: The Bidder shall propose a colour scheme for each of the Parks. The Contract Administrator reserves the right to alter colours for the playstructure and/or swings at the time of award.

Revise E2.3.1(b) and E2.3.1(b)(i) to read:

(b) This specification shall cover the supply and installation of a complete swing standards at Berkshire Park (Type 2);

(i) **Type 2** – 10ft. high, 6 seats

Three Leg Heavy Duty Swing Frame, complete with four (4) slash-proof rubber belt seats, **two** (2) slash-proof rubber, enclosed infant seats heavy duty chain, swing hangers and hammerlocks

Revise E2.3.3(b)(i) to read:

- (i) Swing set – Type 2

Revise E2.6.2 to read:

E2.6.2 **Materials and Constructions Methods:**

Add E2.6.2(b) and E2.6.2(c) as follows:

- (b) All posts and supports shall be centred in the concrete footing such that there is a complete collar of concrete around each post and support. Where posts are not perfectly centred there should be a minimum of 2" (two inches) of concrete at any point around the post.
- (c) All concrete footings shall be a minimum of 3' (three feet) depth, or in accordance with Manufacturers specifications or whichever is greater.