



- NOTES:**
1. PEDESTAL TO BE 7 GAUGE ATMOSPHERIC CORROSION RESISTANT STEEL, SUITABLE FOR HOT DIP GALVANIZING
 2. INSIDE PANEL MAY BE I2 GAUGE
 3. DOORS SHALL BE INTERCHANGEABLE
 4. ALL SEAMS SHALL BE CONTINUOUS WELD
 5. ALL WELDS & EDGES SHALL BE GROUND SMOOTH.
 6. PEDESTAL TO BE HOT DIPPED GALVANIZED TO CSA STANDARD G164-M1981, NET RETENTION OF 600 g/m
 7. MINIMUM DIAMETER OF FLAT PORTION INSIDE CUP WASHER TO ACCOMMODATE STANDARD 3/8" SOCKET
 8. FOR SPECIFICATION DETAIL CLARIFICATIONS, CONTACT THE CITY OF WINNIPEG, TRAFFIC SIGNALS DESIGNER AT 986-4195.
 9. ALL BOLTS AND NUTS SHALL BE STAINLESS STEEL-(S. S.) 316 TYPE.

		LOCATION APPROVED			THE CITY OF WINNIPEG PUBLIC WORKS DEPARTMENT TRANSPORTATION ENGINEERING DIVISION	SCALE 3" = 1'-0" DRAWING NO. ST-34
		UNDERGROUND STRUCTURES COMMITTEE _____ DATE _____ APPROVED BY				
		TRAFFIC SIGNALS ENGINEER _____ DATE _____ RELEASED FOR CONSTRUCTION				
		MANAGER OF TRANSPORTATION ENGINEERING _____ DATE _____ DRAWN BY N.C. 95/08/03 PRELIM. CHK. _____ DATE _____		DESIGNED BY _____ CHECKED BY _____		
1	03/03/07	ADDED/CORRECTED NOTES AND DETAILS				
No	DATE	REVISIONS	BY			