



- I USE TYPE V CEMENT INSIDE & OUTSIDE
- II 1" THICK EXTERIOR COATING FOR ALL PIPES & FITTINGS

MICROFILMED APR 10 1978

QTY.	MK. No.	DIA.	DESCRIPTION	ENDS	DWG. No.
1	27	24"	CLOSURE PIECE 9.09'	P.S.E./S	
1	26	24"	CLOSURE PIECE 10.03'	P.S.E./B	
1	23	24"	SHORT PIPE 10'-0" LG. CL-12	S/B	
1	22	24"	SHORT PIPE 15'-0 1/2" LG CL-12	S/B	
1	21	20x12"	CONCENTRIC REDUCER 4' 5" LG	P.S.E./P.S.E.	56-0148-10
1	20	24"x20"	CONCENTRIC REDUCER 2'-3" LG. SEE DETAILED DWG. OF MK-20 AT BACK OF SCHEDULE	S/R.S.E.	56-0148-9
1	19	24"	SHORT PIPE 16'-0" LG. 9/16" I.P.T. (TOP) & 15'-6" FROM S. CL-12	S/B	
1	18	24"	STD PIPE 20'-0" LG. 9/16" I.P.T. (TOP) & 6'-1 5/8" FROM S. CL-12	S/B	
2	14	24"	15'-00' BEVEL ADAPTOR	S/B	5111-16-24
32	STD	24"	HYPRESCON STD. PREST. LINED CYL. PIPE 20'-0" LG. C-301(L) CL-12	S/B	5002-04-24-1

REV.	DATE:	RECORD OF CHANGE	BY:
CITY OF WINNIPEG 24" φ FEEDERMAIN ON SARGENT AVE.			
Scale: N.T.S.		Date: SEPT. 23 1974	
Drawn by: K.T.P.	Checked by: H.B.	Approved by: K.H.	Drawing No. 56-0148-3
			Rev.

REFERENCE DRAWING ONLY

40 DILLON ACAD FILE: G:\CAD\44330\Draw\Current\REFERENCE ONLY 56-0148-3.dwg 11/12/2008