

ISSUES:		
NO.	DATE	DESCRIPTION
1	SEP. 24, 2010	ISSUED FOR TENDER
2	DEC. 16, 2010	ISSUED FOR CONSTRUCTION

© COPYRIGHT MURPHY & MURPHY ARCHITECT 2009
NOT TO BE REPRODUCED WITHOUT CONSENT OF ARCHITECT.

VanBoxmeer & Stranges Ltd.
STRUCTURAL ENGINEERS
458 Queens Ave, London, ON, Canada N6B 1X9
tel. (519) 433-4661 fax. (519) 433-6420
E-mail vbands@vbands.com

MURPHY & MURPHY ARCHITECT INC.
775 WATERLOO STREET, LONDON, ONTARIO N6A 3W5
PH: (519) 433-5161 FAX: (519) 433-5163

A	A. Detail Number
B	B. Drawing Number - Where Detail Found

CONTRACTOR SHALL CHECK ALL DIMENSIONS ON THE DRAWINGS AND REPORT ANY DISCREPANCIES TO THE ARCHITECT BEFORE PROCEEDING. ALL DRAWINGS AND SPECIFICATIONS ARE PROPERTY OF THE ARCHITECT AND MUST BE RETURNED AT THE COMPLETION OF THE WORK. DRAWINGS ARE NOT TO BE SCALED. USE ONLY THE LATEST REVISED DRAWINGS OR THOSE THAT ARE MARKED "MAILED FOR CONSTRUCTION". ANY UNAUTHORIZED USE IS PROHIBITED. AREA CALCULATIONS ARE APPROXIMATE.


PROJECT NAME:
NEW WINNIPEG STATION No. 27 PROJECT
WINNIPEG, MANITOBA

DRAWING TITLE:
ROOF FRAMING PLAN

PROJECT NORTH:

STAMP:


SCALE:	PROJECT NO.:
DATE:	10123
ISSUED:	FILE NAME:
MAY 20 2010	
DRAWN BY:	DRAWING NO.:
DZ	S13
CHECKED BY:	
RAS	



ROOF FRAMING PLAN.
SCALE: 1:75 NOTE: ALL MASONRY WALLS TO BE MW190A U.N.O.

- ROOF FRAMING PLAN NOTES**
- SEE S1.4 FOR DESIGN LOADS AND LINTEL SCHEDULE
 - TYPICAL APPARATUS BAY ROOF CONSTRUCTION: 38mm STEEL ROOF DECK WITH FLUTES AT 152 mm o/c 0.91 NCT RD 938 BY VIC-WEST OR APPROVED EQUAL, ON PURLINS ON STEEL TRUSSES.
 - SEE ARCHITECTS DRAWINGS FOR EXACT LOCATIONS OF ALL MASONRY WALLS. DESIGN CORESLAB FOR ALL SHOWN ON ARCHITECTS DRAWINGS IN ACCORDANCE WITH THE LOADS SHOWN ON S1.3
 - THIS BUILDING REQUIRES THE MASONRY FOR LATERAL STABILITY. WALLS MUST NOT BE REMOVED WITHOUT APPROVAL FROM THE STRUCTURAL ENGINEER.
 - AT ALL LOCATIONS NOTED THUS 'MC', CONNECTION TO BE DESIGNED FOR THE FULL MOMENT AND SHEAR CAPACITY OF THE SECTION.
 - TYPICAL ROOF CONSTRUCTION: PRECAST CONCRETE PLANKS BEARING ON 200 CONCRETE BLOCK. ANCHOR SLAB TO TOP OF WALL.
 - ALL CONSTRUCTION TO BE AS PER THE LATEST VERSION OF THE N.B.C.
 - MASONRY WALLS TO BE CONSTRUCTED OF HOLLOW MASONRY UNITS UNITS HAVING A MINIMUM COMPRESSIVE STRENGTH OF 15 MPa ON NET AREA. MORTAR TO BE TYPE S. INSTALL MASONRY REINFORCING @ 600 o/c HOT DIP GALVANIZED AFTER FABRICATION.

- ALL STEEL LINTELS TO HAVE A MINIMUM BEARING OF 200 EACH END. FILL MASONRY SOLID BELOW BEARING OF LINTEL.
- ALL MASONRY REINFORCING TO BE HOT DIP GALVANIZED AFTER FABRICATION, SEE DRAWING S6 FOR MASONRY REINFORCING DETAILS.
- ALL OPENINGS THROUGH THE PRECAST CONCRETE FLOOR SLABS TO BE APPROVED BY THE PRECAST CONCRETE FLOOR SLAB SUPPLIER.
- NOTE CORESLAB SLOPES TO LOW POINT. FINISHED TOP OF CORESLAB TO BE 4200 ABOVE FLOOR. SLOPE CORESLAB BY AMOUNT SHOWN THUS $\frac{xxx}{xxx}$ ON PLAN.
- CIRCULAR HOLES IN THE CORESLAB SHOWN ON PLAN THUS \bigcirc XXX. CO-ORDINATE LOCATION AND SIZE WITH THE MECHANICAL AND ELECTRICAL DRAWINGS.
- CO-ORDINATE ALL OPENINGS WITH THE MECHANICAL AND ELECTRICAL DRAWINGS.



MECHANICAL UNIT PLATFORM PLAN.
SCALE: 1:75