

DETAIL-REINFORCED CONCRETE FLOOR-WITHOUT CURB SCALE: 1:5

102 50 DIA. WHERE SPECIFIED: PROVIDE CURB AND 20mm CHAMFER FOR CLEANUP AND WASH DOWN PROTECTION (TYP.). REINFORCE WITH 1−10M TIE (TYP.) □ GALVANIZED PIPE SLEEVE (TYP.) FIRE STOP (TYP.) ROUGHEN EXISTING CONCRETE AND APPLY EPOXY BONDING AGENT (TYP.). LOCATE AND POSITION HOLE FOR CONDUIT CLEAR OF REINFORCEMENT (TYP.).

DETAIL-REINFORCED CONCRETE FLOOR-WITH CURB SCALE: 1:5



DETAIL - CONCRETE JOIST FLOORS SCALE: 1:10



DETAIL - PRECAST DOUBLE TEE CONCRETE FLOOR SCALE: 1:10

> **APEGIN** Certificate of Authorization SNC-Lavalin Inc. No. 4489

NO. REVISIONS

		_			•))	SNC-LAVALIN INC. 148 Nature Park Way	ENGINEER'S SEAL
					SNC+LAVALIN	Winnipeg, MB, Canada R3P 0X7 204-786-8080	ORIGINAL DRAWING
					DESIGNED BY:	CHECKED BY:	SEALED BY:
					N. KEHLER	R. BEAN	R. C. BEAN
					DRAWN BY:	APPROVED BY:	SNC-LAVALIN
					S. FUNK	C. REIMER	2011/03/23
					SCALE: AS SHOWN	RELEASED FOR CONSTRUCTION	REV. 00
						BY: N. HARRINGTON	
					DATE: 2011/02/22	DATE: 2011/04/01	
00	ISSUED FOR TENDER, BID OPP. 209-2011	2011/04/01	NK	l nn	CONSULTANT NO :	0400 4700 0000	1
NO.	REVISIONS	DATE	DESIGN	CHECK	112577-0106-47DD-0008		

DATE DESIGN CHECK

NOTES:

. LOCATE REINFORCING IN THE EXISTING FLOOR AND ROOF SLABS WITH A

2. MARK OUT LOCATIONS INTENDED FOR OPENINGS AND CONFIRM ACCEPTABILITY

2. DRILL A PILOT HOLE INTO THE EXISTING CONCRETE ADVANCING THE DRILL BIT TO FULL DEPTH OF THE REQUIRED OPENING. IF REINFORCING IS ENCOUNTERED,

TERMINATE DRILLING OF THE PILOT HOLE AND RELOCATE THE OPENING CLEAR OF THE REINFORCING, USE A STANDARD HARDENED CARBIDE TIPPED CONCRETE BIT. DO

NOT USE A CORE DRILL THAT CAN INTERCEPT AND CUT THE REINFORCING WHILE INSTALLING THE PILOT HOLE. PILOT HOLES FOR OPENINGS SHOULD BE POSSIBLE UP TO 38mm IN DIAMETER. LARGER HOLES UP TO 50mm IN DIAMETER MAY BE CORED

CONCRETE REINFORCING BAR LOCATOR PRIOR TO DRILLING.

WITH CONTRACT ADMINISTRATOR PRIOR TO DRILLING.

FOLLOWING COMPLETION OF A SMALLER PILOT HOLE.

REGARDING PLACEMENT OF THE OPENINGS.

3. ADVISE THE CONTRACT ADMINISTRATOR IMMEDIATELY IF THE REQUIRED

ADMINISTRATOR WILL REVIEW THE SITUATION AND MAKE A DETERMINATION

OPENINGS CANNOT BE FIELD ADJUSTED TO CLEAR THE EXISTING REINFORCEMENT AND AWAIT FURTHER INSTRUCTIONS. THE CONTRACT

Winnipeg THE CITY OF WINNIPEG WATER AND WASTE DEPARTMENT

SOUTH END WATER POLLUTION CONTROL CENTRE ESSENTIAL SYSTEM UPGRADES INSTALLATION DETAIL TYPICAL FLOOR PENETRATION REQUIREMENTS

SHEET REV. SIZE 001 | 00 | A1

1-0102A-E0008-001-00.dwg