







CONSTRUCTION NOTES

- 1. INSTALL DETECTABLE WARNING SURFACE TILE AT CURB RAMP AS PER SD-22844 (TYP.)
- REMOVE EXISTING CONCRETE SIDEWALK AND CURB AND CONSTRUCT NEW MONOLITHIC CURB AND SIDEWALK WITH BLOCKOUTS (SEE DETAIL)
- 3. REMOVE EXISTING INTERLOCKING PAVING STONE SIDEWALK AND CURB AND CONSTRUCT NEW MONOLITHIC CURB AND SIDEWALK WITH BLOCKOUTS (SEE SE-22-124)
- 4. REGRADE EXISTING PAVING STONES
- CONSTRUCT 12.75 m³ SILVA CELL WITH A SUMP PIT, TREE WELL CURBING, ADA COMPLIANT - 8709-A 48"x48" GRATE AND FRAME; NEW TREE TO BE SUPPLIED AND PLANTED BY OTHERS (SEE SE-22-125)
- 6. CONSTRUCT 25.5 m³ SILVA CELL WITH DRAINAGE CONNECTED TO EXISTING CB, AND ADA COMPLIANT GRATES AND FRAMES; NEW TREES TO BE SUPPLIED AND PLANTED BY OTHERS (SEE SE-22-125)
- 7. TREE REMOVAL AS PER CW 3010-R4
- 8. REMOVE TREE WELL CURBING AND SOIL AND CONSTRUCT NEW MONOLITHIC CURB AND SIDEWALK (SD-228B)

GENERAL NOTES

- A. UTILITY DIMENSIONS ARE TO BACK OF CURB
- B. ALL CURB RADII UNDER 15.0m SHALL BE MODIFIED
- C. PAVING BAND ALIGNMENT TO BE DIRECTED BY CONTRACT ADMINISTRATOR
 D. CURB REPLACEMENT AS DIRECTED BY CONTRACT ADMINISTRATOR
- E. CONTRACTOR TO CONFIRM THE LOCATION OF ALL UTILITIES/SERVICES IN THE
- F. FIELD PRIOR TO CONSTRUCTIONG. USE EXTREME CAUTION WHEN WORKING ABOVE UTILITY VAULTS
- H. CONTRACTOR TO TAKE PRECAUTIONARY STEPS TO PROTECT EXISTING TREES WITHIN THE CONSTRUCTION LIMITS AS PER CW 1140
- I. CURB REPLACEMENT AS DIRECTED BY CONTRACT ADMINISTRATOR
- J. PAVING STONE INSTALLATION AS DIRECTED BY CONTRACT ADMINISTRATOR K. NEW TREES SUPPLIED AND PLANTED BY OTHERS, MIN. 1500 FROM BACK OF
- L. ADJUST ALL CURB STOPS AND WATER VALVES TO GRADE

PRELIMINARY

NOT TO BE USED FOR CONSTRUCTION

METRIC

RIC L

WHOLE NUMBERS INDICATE MILLIMETERS DECIMALIZED NUMBERS INDICATE METERS TENDER NO. 333-2022

THE CITY OF WINNI

Winnipeg

THE CITY OF WINNIPEG
PUBLIC WORKS DEPARTMENT

ELLICE AVENUE

FROM COLONY STREET TO KENNEDY STREET
SIDEWALK RENEWAL & SILVA CELL INSTALLATION

SECTION DRAWINGS & DETAILS

SHEET 2 OF 3

CITY DRAWING NUMBER SE-22-124

-	HYDRANT	+		LDS/WWS			CONCRETE	LOCATION APPROVED
8	VALVE	•		WATERMAIN			CONCRETE SIDEWALK	UNDERGROUND STRUCTURES
Q	CURB STOP	•		GAS	— …—		ASPHALT	ONDERGROUND OTHEOTORIES
0	MANHOLE	•		TRAFFIC SIGNALS		⊠	UTILITY BOX	SUPR, U/G STRUCTURES DATE
	CATCH BASIN			HYDRO/STREET LIGHT			BRICK	COMMITTEE
Δ	CURB INLET	A		MTS/SHAW				NOTE:
$\overset{\mathbb{I}}{\Diamond}$	HYDRO POLE	••		CURB RENEWAL				LOCATION OF UNDERGROUND STRUCTURES AS
ر ٥	LIGHT STANDARD	••		PROPERTY LINE				SHOWN ARE BASED ON THE BEST INFORMATION AVAILABLE. BUT NO GUARANTEE IS GIVEN
	TRAFFIC SIGNAL POLE	●→		RAMP CURB				THAT ALL EXISTING UTILITIES ARE SHOWN OR THAT THE GIVEN LOCATIONS ARE EXACT.
#	SURVEY BAR	+	231.000	ELEVATIONS	(31.000)			CONFIRMATION OF EXISTENCE AND EXACT
	GEODETIC BENCH MARK		©	TREE	@			LOCATION OF ALL SERVICES MUST BE OBTAINED FROM THE INDIVIDUAL UTILITIES
EXISTING	LEGEND - PLAN	PROPOSED	EXISTING	LEGEND - PLAN	PROPOSED			BEFORE PROCEEDING WITH CONSTRUCTION.

B.M. IB @ NW CORNER ELLICE AVE & KENNEDY ST ELEV. 232.359				ENGINEERIN	ENGINEER'S SEAT	
				TECHNOLOGY SEI 106 - 1155 PA	M.E.	
				DESIGNED C.W.	CHECKED R.W.	WARKENTIN S
				DRAWN C.W.	APPROVED BY	31162 31162
				HOR. SCALE: 1:250		2022-06-13
1.	SUBMIT FOR PLAN APPROVAL	22/06/01	C.W.	VERTICAL: 1:10		
NO.	REVISIONS	DATE	BY	DATE 2022/06/09		