## **CRANE DATA SHEET 3**

## Location: 195 Tecumseh Street

- 1. Capacity: Hoist(s) \_\_\_\_\_5 Ton\_\_\_ Bridge Span: \_50 ft\_\_\_\_\_
- 2. Required Hook Lift \_\_\_\_\_15\_\_\_ft. \_\_\_0\_\_in. Minimum
- 3. Approximate Length of Runway: \_\_\_\_\_145 ft\_\_\_\_\_
- 4. Number of Cranes on Runway: <u>single</u>
- 5. Service Information: CMAA Class <u>C</u>
- 6. Ambient Temperature in Building: Max: <u>120°F</u> Min: <u>50°F</u>
- 7. Material Handled: <u>\_\_\_\_\_Road equipment and components</u>\_\_\_\_\_
- 8. Speeds Required: a) Hoist <u>Two speed 24/3.9</u> fpm.
  - b) Trolley <u>20 / 5</u> fpm. or VFD infinite control

c) Bridge <u>60 / 10</u> fpm or VFD infinite control

- 9. Crane to Operate: Indoors only
- 10. AC Power Volts 230 Phase 3 Hertz 60 Breaker 60 amp
- 11. Provide dedicated contactor with lock out.
- 12. Method of Control: Pendant  $\boxtimes$  Remote  $\boxtimes$
- 13. Location of Pendant Control: Handheld Pendant on roller track
- 14. Remote Control Functions

Hand held radio controlled remote with encoded communication to crane. Provide spare remote. Operator key required.

- 15. Lighting: Four LED lighting fixtures 8000 Lumens each required to be mounted to the crane bridge. Align lights with existing ceiling lights.
- 16. Shop drawings: Provide shop drawings with all structural, mechanical and electrical details to the engineer. Provide data sheets for hoists, trolleys, end trucks and related drives. Provide data sheet for pendants, remote controls, duct-o-bars, light fixtures, switches and contactors.