FORM N: DETAILED SPECIFICATIONS 22033

3-WHEELED SPORTS FIELD GROOMER

1. INSTRUCTIONS FOR COMPLETION OF SPECIFICATIONS

- 1.1 All items in these specifications should be answered indicating compliance or non-compliance.
- 1.2 **Bidder shall state "yes" for compliance or state "deviation"**, or give a reply where requested to do so. Deviations and/or equivalents shall be clearly stated and fully detailed. Deviations and/or equivalents will be considered subject to evaluation. In every instance where a brand name or design specifications is used, the City will also consider deviations and/or equivalents.
- 1.3 Lengthy explanations of deviations may be included in a separate document and must reference the appropriate Detailed Specification.
- 1.4 Each Proponent is required to fill in every blank. Failure to do so may be used as a basis for rejection of bid.
- 1.5 It will be the responsibility of the Proponent to inform the City of any errors or omissions in these Detailed Specifications, for under this Contract, the Contractor shall be held responsible to ensure that the manufacturer will be responsible for the design, performance, reliability and satisfactory operational function of the unit.

2. DESCRIPTION OF EQUIPMENT

- 2.1 These specifications describe <u>3-Wheeled Sports Field Groomer</u> and other equipment and features as specified herein.
- 2.2 The <u>**3-Wheeled Sports Field Groomer**</u> shall be a new **2022** model year or newer.
- 2.3 The <u>3-Wheeled Sports Field Groomer</u> and all other items/components shall be the manufacturer's latest model. The equipment shall be furnished complete and ready for operation. Any parts or accessories not specifically mentioned, but which are required to complete and place the equipment and associated attachments in successful operation shall be furnished as though specifically mentioned in these specifications. The equipment and associated attachments, and all parts thereof, shall conform in strength and quality of material and workmanship, to the best standards and engineering practice of the industry.
- 2.4 The ratings specified herein merely state the minimum values acceptable to the City, not implying that those values are sufficient for the design of the particular equipment being bid.

3. OTHER SPECIFICATIONS AND STANDARDS

- 3.1 All applicable SAE Standards form an integral part of the vehicle specifications and shall have precedence in any conflict concerning minimum acceptable standards.
- 3.2 <u>Where applicable</u>, the <u>**3-Wheeled Sports Field Groomer**</u> shall comply with the applicable regulations:

Transport Canada, National Safety Mark, NSM: http://www.tc.gc.ca/eng/acts-regulations/acts-road.htm

Manitoba Safety and Health Regulation, Parts 12, 16, 22: https://www.gov.mb.ca/labour/safety/pdf/1_2016_wsh_ar_oc.pdf

Canadian Motor Vehicle Safety Standards C.M.V.S.S. Motor Vehicle Safety Regulations (justice.gc.ca)

Manitoba Highway Traffic Act regulations and requirements including, but not limited to, a Manitoba Government Inspection with Safety Sticker. http://web2.gov.mb.ca/laws/regs/index.php?act=h60

Canadian Standards Association, CSA: http://www.csagroup.org/

Under Writers of Canada, U/L: Underwriters Laboratories of Canada (ULC)

Society of Automotive Engineers, SAE: <u>http://www.sae.org/</u>

City of Winnipeg Lighting Visibility Standard: http://winnipeg.ca/matmgt/pdfs/PublicWorksEquipLightingVisibility.pdf

Manitoba Building Code: https://web2.gov.mb.ca/laws/regs/current/_pdf-regs.php?reg=31/2011

4. FUEL

4.1 The equipment shall be fully fuelled upon delivery (no exceptions).

5. REFERENCES

5.1 Provide five (5) references where this equipment is used in a working environment where climatic conditions are similar to the City of Winnipeg.

6. MAKE & MODEL

6.1 State year, make and model being bid:

Model	Year [.]
moder	rour.

Make:

Model:

7. PERFORMANCE RELIABILITY

- 7.1 The responsibility for the design of the <u>3-Wheeled Sports Field Groomer</u>, its performance and reliability shall rest upon the Contractor.
- 7.2 The term "repeated failures" as used herein is defined to mean that the same component, subassembly, or assembly develops repeated defects, breakdowns and/or malfunctions rendering the vehicle inoperative, or requiring repeated shop correction, service and/or replacement during the warranty period applicable for said component, subassembly, of assembly. Minor items or ordinary service adjustments are not included, or considered under the scope of "repeated failures", as well as other factors, such as operational damage due to accidents, misuse or lack of proper maintenance, service and lubrication attention by not following the manufacturer's preventative maintenance schedule.
- 7.3 Where the <u>3-Wheeled Sports Field Groomer</u> develops "repeated failures" in service, the Contractor shall make any necessary engineering changes, repairs, alterations or modifications in order to guarantee reliability of performance.
- 7.4 The equipment shall be capable of consistent top performance in City of Winnipeg Environment. Note: The City of Winnipeg has four seasons with ambient temperatures ranging from approximately 90°F (32°C) to -40°F (-40°C).

8. SERVICE FACILITY

8.1 For the purpose of warranty repairs, the Bidder shall have an authorized service facility. The facility, or a portion thereof, shall be dedicated to the service and maintenance of the type equipment being offered. Bidders shall provide a description of the service facility including, but not limited to, number of qualified service staff, years of service experience, and general service capabilities within three (3) Business Days upon request of the Contract Administrator

9. QUALIFICATIONS OF MANUFACTURER & CONTRACTOR

- 9.1 The manufacturer of the <u>3-Wheeled Sports Field Groomer</u> shall have five (5) years continuous experience manufacturing <u>3-Wheeled Sports Field Groomer</u>.
- 9.2 The manufacturer shall have in effect a documented quality control program ensuring that the quality of materials and workmanship, including welding, conforms to the best standards and engineering practice of the industry.
- 9.3 The Contractor shall have five (5) years continuous experience servicing, repairing and maintaining <u>3-</u> <u>Wheeled Sports Field Groomer</u> of the type being offered.

10. SPECIFICATIONS

10.0 **Requirement:**

3-Wheeled Sports Field Groomer with the following attachments:

- Front Hydraulic Flex Blade
- Flex Groomer
- Nail Drag
- Automat Drag Mat

10.1	Equipment Make	State: make:	
10.2	Equipment Model	State: model:	
10.3	Equipment Model Year	State: model year:	
	Engine		
10.4	Туре	Vanguard, V-Twin cylinder, 4-cycle or equivalent State: Type:	
10.5	Horsepower	Approximately 18 HP (13.4 kW) State: horsepower:	
10.6	Displacement	Approximately 34.78 (570 cc) State: displacement:	
10.7	Hour Meter	Hour meter	
10.8	Ignition	Electronic	
10.9	Mounting	Base mounted engine and pump	
		Four (4) isolation mounts	
10.10	Cooling System	Air-cooled	
10.11	Engine Lubrication	Full pressure lubrication	
10.12	Oil Filter	Oil filter	

10.13	Oil Capacity	Approximately 1.75 quart (1.8 litre) State: capacity:	
	Air Cleaner System		
10.14	Air Cleaner	 Engine mounted Remote air intake State: system details: 	
	Electrical		
10.15	Battery	 12-Volt 15 Amps CCA State: Volt: Amp: CCA: 	
10.16	Starter	 Electronic ignition 12-Volt electric Dash mounted ignition switch Neutral interlock switch Seat switch Provision for light kit 	
	Fuel		
10.17	Fuel Tank Capacity	Approximately 5.0 US Gallon (18.9 litre) State: capacity:	
		Note: Fully fuelled upon delivery	
	Traction Drive		
10.18	System	Variable displacement hydraulic pump	
10.19	Hydraulic Cooling System	Full flow filter with oil cooler	
10.20	Hydraulic System Capacity	Approximately 5.0 US Gallon (18.9 litre) State: capacity:	
10.21	Ground Speed	Approximately: • Forward speed 0 – 16 km/h • Reverse speed 0 – 7 km/h	
	Tires		
10.22	Tires	Turf State: type and size:	
	Brakes		
10.23	Service Brakes	Hydrostatic State: type:	
10.24	Parking Brake	Hand operated	

	Steering		
10.25	Steering	Hydraulic power steering	
	Controls		
10.26	Controls	 Hand operated choke, throttle, and hydraulic control for raising/lowering with float Foot pedal controls traction forward and reverse operations Front and rear hydraulic lift and lower controls 	
	Seat		
10.27	Seat	 High back cushion with drain hole Front-back adjustment Arm rests 	
	Dimensions		
10.28	Width	Approximately 58 in. (1470 mm) State: width:	
10.29	Length	Approximately 67.5 in. (1715 mm) State: length:	
10.30	Height	Approximately 45.25 in. (1149 mm) State: height:	
10.31	Wheelbase	Approximately 42.75 in. (1080 mm) State: wheelbase:	
10.32	Ground Clearance	Approximately 6.0 in. (152 mm) State: clearance:	
10.33	Weight (Dry)	Approximately 930 lbs. (422 kg) State: dry weight:	
	Attachments Note: Attachments to be priced only as indicated on Form B: Prices		
10.34	Quick Attach System	FrontRear	
10.35	Rear Remote Hydraulics	Quick-connect design	
10.36	Remote Hydraulic Flow Switch Kit	 Allow operator to toggle between rear and front powered attachments 	
10.37	Variable Orifice Kit	 Slows hydraulic lift and lower for increased precision and accuracy when using attachments 	
10.38	Front Lift Frame Assembly	Front quick attach system mounting assembly and hydraulic components	

10.39	Front Hydraulic Flex Blade	 Quick attach system compatible Designed for leveling, packing, and smoothing uneven areas in one pass 	
10.40	Rear Nail Drag	 Quick attach system compatible Pivots to follow the contours of uneven field surface Use to scarify, loosen, or weed before smoothing Easily adjust nail pattern and depth 	
10.41	Rear Flex Groomer	 Quick attach system compatible Flexible Approximately 72 in. (1820 mm) width Mounts to nail drag for single-pass infield scarification and grooming Lock-out position to restrict use without tools or removal 	
10.42	Rear Automat Drag Mat	 Quick attach system compatible Approximate size 78 x 18 in. (1980 x 460 mm) Steel drag mat is controlled by and works together with nail drag for single-pass scarification and finish grooming Drag mat automatically engages the infield as the nail drag is lowered via the rear quick attach system Lock-out position when use is not required 	
	Safety		
10.43	Beacon	 Amber LED Beacon Class 1 SWS 23815 or Grote 78033 Wired directly to the ignition i.e. no switch. Beacon must also come with a <u>safety guard</u> – Grote 98470 	
10.44	Fire Extinguisher	 2.5 lbs. High volume ABC type Securely mounted with quick release	
10.45	Battery Disconnect Switch	Lockable with padlock	
10.46	Horn	Horn	
10.47	Back Up Alarm	 Approximately 95 – 112 dB Protected from damage State: dB(A): 	
10.48	Slow Moving Vehicle Sign	Mounted	

11.0 WARRANTY:

11.1	All warranty information shall be detailed and include all exclusions.	
	The Contractor shall provide all published warranty information upon delivery of the equipment.	
	Bidder shall state all warranty information.	
11.2	The warranty for the <u>3-Wheeled Sports Field Groomer</u> shall cover the complete equipment, and all parts thereof against any defects of workmanship, construction and materials.	
	Any equipment that has become defective during said warranty period and has not proven to have been caused by negligence on the part of the user shall be repaired or replaced at no cost to the City.	
	The warranty shall be effective from the date the equipment is put into service by the City of Winnipeg	
11.3	Basic Vehicle (Comprehensive) State: Terms:	
12.0	DELIVERY:	
12.1	Delivery Point:	
	The complete unit shall be serviced, ready for operation and delivered F.O.B. with the freight prepaid, including invoice and N.V.I.S. (if applicable) to the WFMA 185 Tecumseh Street, Winnipeg MB.	
12.2	Delivery Time:	
	Equipment shall be delivered between 8:00 am and 2:00 pm on Business Days.	
	State: earliest delivery time from date of award:	
12.3	Delivery Contact:	
	The Contractor shall contact the Contract Administrator prior to delivery of the equipment.	
12.4	<u>P.D.I:</u>	
	A pre-delivery inspection shall be performed by the Contractor on the equipment. Proof upon inspection including completed check list	

13.0 **MANUALS**:

13.1 Manuals:

The following manuals shall be supplied with the units when delivered:

Operator - Two (2) Copies

- One (1) copy shall be sent to the Equipment Operator Training Branch
- One (1) copy to be left with the equipment

Parts and Service

• One (1) complete set including preventative maintenance schedules

Note: CD or USB flash drive is preferred where available

14.0 **PARTS/LABOUR PRICING:**

15.0 **FIRST SERVICE PREVENTATIVE MAINTENANCE KIT:**

- 15.1 <u>If applicable</u>, in order to assure minimum downtime of the Equipment in future service, the Contractor must provide one (1) complete replacement set of new OEM filters for each unit purchased. The set of required filters shall include (if applicable to the equipment type) air, fuel, oil, transmission, cab and hydraulic, or otherwise all known necessary common replacement filters required for the first preventative maintenance servicing and first transmission service.
- 15.2 The Contractor must provide a list of Factory recommended lubricants to be used with the equipment, as well as a complete cross reference guide for all warranty approved lubricants and filters that can be used during Preventative Maintenance servicing.