



# ADDENDUM NO. 1 BID OPPORTUNITY NO. 105-2004

## ROOF REPLACEMENT AT BRONX C.C. – 131 CHELSEA PLACE

### **URGENT**

**PLEASE FORWARD THIS DOCUMENT TO  
WHOEVER IS IN POSSESSION OF THE BID  
OPPORTUNITY**

ISSUED: April 13, 2004  
BY: Coleen Groening /clg  
TELEPHONE NO. (204) 986-2491

**THIS ADDENDUM SHALL BE INCORPORATED  
INTO THE BID OPPORTUNITY AND SHALL  
FORM A PART OF THE CONTRACT  
DOCUMENTS**

Template Version: 20040128

---

**Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Bid may render your Bid Submission non-responsive.**

---

### **PART B – BIDDING PROCEDURES**

**Revise:** B2.1 Submission Deadline to read:

B2.1 The Submission Deadline is 12:00 noon Winnipeg time, **April 21, 2004.**

### **PART E – SPECIFICATIONS**

**Add:** .16 to Materials (page 3 of 8)

.16 METAL SIDING

.16 This shall be 24 gauge Vicwest CL815R or approved equal. Color is to be Stelco 8000 series black.

**Delete:** .07 of Description of Work (page 6 of 8)

**Add:** .27 to Description of Work (page 8 of 8)

.27 The existing wood siding band is to be removed and the new metal siding band installed. The new siding is to extend to the top of the parapets and to the same bottom elevation as the existing wood band. The top of the siding is to be secured to the parapet. The bottom and middle is to be secured to a new  $\frac{3}{4}$ " deep 18 gauge galvanized sheet metal hat bars of which are to be securely fastened to the existing concrete block walls. Secure the hat bars with #10 Tapcon screws spaced to more than 16" on centre staggering the screws from the top leg to the bottom leg. Install a matching color and thickness drip flashing along the bottom of the siding to ensure that the gap from the wall to the front face of the siding is closed off. Secure the new siding in place with matching color #10 hex head screws with neoprene washers