


GENERAL NOTES:

1. THE CONTRACTOR IS TO VERIFY INFORMATION ON THE DRAWINGS & REPORT ERRORS TO THE ENGINEER.
2. ROOF ANCHORS ARE DESIGNED FOR A HORIZONTAL LOAD OF 5000 LBS.(UNFACTORED) IN ANY DIRECTION.
3. ACCESS TO THE ROOF WILL BE PROVIDED TO THE CONTRACTOR WHO WILL SUPPLY INFORMATION TO THE ENGINEER ON METHOD OF INSTALLATION REQUIRED SAFETY MEASURES FOR THE WORKERS.
4. ALL TIMBER TO BE A MINIMUM SPF #2 OR BETTER.
5. TIMBER CONNECTORS TO UTILIZE "SIMPSON STRONG TIES", W/ THRU BOLTS OR LAG BOLTS. CONTRACTOR TO INDICATE METHOD THRU SHOP DRAWINGS.
6. ROOF ANCHORS TO BE AS SHOWN ON DETAILS SECURED WITH 6-3/4" BOLTS THRU BASE PLATES. INSTALL ANCHORS WITH FLASHING INCORPORATED INTO THE EXIST. ROOF SYSTEM.
7. THE CONTRACTOR IS RESPONSIBLE TO INSTALL ROOF ANCHORS & TO INCORPORATE THEM IN THE EXISTING ROOF SYSTEM & ENSURE THAT THERE IS NO ROOF LEAKAGE.
8. ROOF ANCHORS TO BE AS DISTRIBUTED BY IMPERIAL METAL OR APPROVED EQUAL.
9. SHOP DRAWINGS OF ROOF ANCHORS TO BE SUBMITTED FOR ENGINEER'S REVIEW.

ROOF PLAN

SCALE: 1/16"=1'-0"



CHARLESON ENGINEERING LTD.

101-1200 Pembina Hwy.
WINNIPEG, MANITOBA
TEL (204) 895-1474

**WESTDALE
COMMUNITY CENTRE
PARKS, CITY OF WINNIPEG**

**FALL ARREST ROOF ANCHORS
ANCHOR LOCATIONS**

SCALE:
AS SHOWN

DATE:
NOV., 2014

DESIGNED BY:
D.C.

DRAWN BY:
LDW

SHEET:

**WD-S-01
RI**