

**Part 1            General**

**1.1                SCOPE**

- .1        This section includes requirements for a secure safe to be installed within the Kiosk building and concrete foundation slab.
- .2        Coordinate installation location and installation requirements with concrete slab installations and kiosk supplier.

**1.3                SHOP DRAWINGS**

- .1        Submit shop drawings in accordance with E3 – Shop Drawings.
- .2        Indicate dimensions, materials, finishes, locking hardware and installation requirements.

**1.4                DELIVERY, STORAGE, AND HANDLING**

- .1        Deliver, handle, store and protect materials of this section until final installation of kiosk is completed, including temporary weather protection.

**Part 2            Products**

**2.1                MANUFACTURED UNITS**

- .1        Safe: Recessed, floor mounted safe: American Security Products Super Brute model B2200E5.
- .2        Interior dimensions: approximately 311 mm x 336 mm x 356 mm deep.
- .3        Lock: Battery powered electronic digital keypad lock mounted on hinged top access door.

**Part 3            Execution**

**3.1                INSTALLATION**

- .1        Cast safe partially in a recess in the concrete slab with the upper part extending to 20 mm below the finished floor level of the kiosk.
- .2        Exact dimensions, location, and installation details to be coordinated by General Contractor with kiosk supplier prior to placing any concrete.

**3.2                PROTECTION**

- .1        Protect safe from physical and environmental damage after installation until final Kiosk installation is complete.

**END OF SECTION**