

427-2015 ADDENDUM 4

TRANSPORTATION MANAGEMENT CENTRE RENOVATIONS 821 ELGIN AVENUE

URGENT

PLEASE FORWARD THIS DOCUMENT TO WHOEVER IS IN POSSESSION OF THE BID OPPORTUNITY

ISSUED: July 22, 2015 BY: Lou Chubenko TELEPHONE NO. (204) 986-2727

THIS ADDENDUM SHALL BE INCORPORATED INTO THE BID OPPORTUNITY AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Bid may render your Bid non-responsive.

PART A - BID SUBMISSION

Replace: 427-2015_Bid Submission with 427-2015_Addendum_4-Bid_Submission. The following is a summary of

changes incorporated in the replacement Bid Submission:

Form A(R1): Add Paragraph 10. Signatures

Form B(R1): Add Items No. 1 to 2 inclusive.

PART B - BIDDING PROCEDURES

Revise: B2.1 to read: The Submission Deadline is 4:00 p.m. Winnipeg time, July 27, 2015.

PART E - SPECIFICATIONS

Add: E8. PLUMBING FIXTURES AND EQUIPMENT – SECTION 22 06 40.13

E8.1 **S-1** - **SINK**:

Franke Commercial #LBS4607-1/1 Single Bowl Countertop Mount Sink, 1 hole, 478 mm (18-13-13/16") x 460 mm (18-1/8") x 178 mm (7") deep, counter mounted, backledge, grade 18-10, 20 GA. (0.9 mm) type 302 stainless steel, self-rimming, satin finish rim and bowls, mounting kit provided, fully undercoated to reduce condensation and resonance, factory applied rim seal, 3-1/2" (89 mm) crumb cup waste assembly with 1-1/2" (38 mm) tailpiece.

American Standard Colony Soft #4175.100 Single Lever Faucet, chrome plated, center hole only, washer-less ceramic disc cartridge, 8.3 LPM (2.2 GPM) outlet, swing spout 239 mm (9-7/16") projection reach, metal lever handle, pull out spray with adjustable spray pattern.

McGuire #LFH170BV, faucet supplies, chrome plated polished brass, commercial duty ¼ turn ball valve angle stops, 13 mm (1/2") I.D. inlet x 127 mm (5") horizontal extension tubes, combination V.P. loose key handle, escutcheon and flexible copper riser. Provide P-Trap, adjustable all metal construction, 38 mm (1-1/2") size, and escutcheon.

E8.2 P-1 - HOT WATER RECIRCULATING PUMP:

Bid Opportunity No. 427-2015 Addendum 4 Page 2 of 2

Taco PNP circulator, 006—PNP, 115v/60hz/1 Phase, 1/40 HP MOTOR, 0.52 A., 2 GPM at 7 feet head complete with digital timer and integral flow check. Wire and connect new re-circulation pump for new Hot Water Tank on cct. PQ-8. Add disconnect to code.

E8.3 **HWT-1 – HOT WATER TANK:**

Giant Model No. 152E, 40.5 imperial gallons, 3Kw, 208V single phase. Confirm voltage with electrical.

E8.4 **LAV-1 – LAVATORY:**

American Standard Ovalyn Universal Access #9482.000.020 Basin, no faucet hole drilling, 489 mm x 400 mm x 140 mm (19-1/4" x 15-3/4" x 5-1/2") high, oval, white, vitreous china, undercounter, rear overflow, #047194-007A undermount clips.

American Standard Colony Soft #2175.504 Single lever faucet, chrome plated, 4" (102 mm) centerset, metal body, 5.7 LPM (1.5 GPM) aerator outlet, 107 mm (4-3/16") projection reach, metal lever handle, less pop-up hole and rod, less drain assembly.

McGuire #155WCC offset open grid drain, chrome plated cast brass one piece top, 17 GA. (1.5 mm) tubular 32 mm (1-1/4") tailpiece. McGuire #FH170BV, faucet supplies, chrome plated polished brass, commercial duty ¼ turn ball valve angle stops, 13 mm (1/2") I.D. inlet x 127 mm (5") horizontal extension tubes, combination V.P. loose key handle, escutcheon and flexible copper riser.

McGuire #8872C P-Trap, heavy cast brass adjustable body, with slip nut, 32 mm (1-1/4") size, shallow wall flange and seamless tubular wall bend.

McGuire PROWRAP #PW2000WC sanitary covering vandal-resistant, flexible seamless moulded closed cell PVC resin, formulated with anti-microbial additive to limit the growth of fungus and bacteria, to exposed piping (to protect against heat/contusions) as per local codes.

Add: E9. ELECTRICAL NOTES

E9.1

E9.2

Wire and connect new re-circulation pump (P-1) for new hot water tank (HWT-1) on cct. PQ-8. Add disconnect to code. Refer to 427-2015_Addendum_3-Drawing_E-2-R3.

In demolition phase, remove panels 100, P and if necessary PP from the existing wall to allow for re-construction of the wall. Panels and wiring to be temporarily supported in such a way as to allow for work on the wall. Re-mount panels, and re-connect affected wiring when wall is complete. **During work on wall, leave feeder and branch circuit wiring connected to panels, and panels energized, if possible.** Refer to 427-2015_Addendum_3-Drawing_E-2-R3.

Add: E10. FINISHES – CARPET TILE - SECTION 09 65 16

E10.1 Carpet – 24 x 24 Shaw Contract Group, Activity Tile #5T089.

Clarification of: 427-2015_Addendum_3-Drawing_E-2-R3 General Note C and 427-2015_Addendum_3-Drawing_E-4-R3 General Note B:

Contractor shall not be responsible as part of this Bid Opportunity to install jacks, switches, bix blocks, patch panels and all necessary equipment and make all connections to ensure fully operational systems.