

SECTION DETAIL

N.T.S.

NOTES:

- 1. CONTRACTOR TO COORDINATE CABLE TRAY WITH THE STRUCTURAL OPENING IN THE LEVEL 200 AND 300 FLOOR. REFER TO STRUCTURAL DRAWING SO3 FOR ADDITIONAL DETAILS.
- 2. REFER TO STRUCTURAL DRAWING SO3 FOR DETAILS ON THE GRIP MESH HOOKING SYSTEM.
- 3. PROVIDE STANDARD DUTY CLOSED MESH, DOUBLE EYE GRIP MESH TO SUPPORT THE POWER AND CONTROL CABLES. GRIP MESH SHALL CONNECT TO THE STRUCTURAL HOOKING SYSTEM.
- 4. PROVIDE A 6" OFFSET FOR THE VERTICAL PORTION OF THE CABLE TRAY. OFFSET TO BE COORDINATED ON SITE WITH THE LIFTING SYSTEM TO ENSURE NO CLASHING.
- 5. ALL FIELD WIRING SHALL BE WITHIN CONDUIT UNLESS STATED OTHERWISE. CONTRACTOR IS RESPONSIBLE FOR PATCHING AND/OR FIRE STOPPING ALL FLOOR/WALL PENETRATIONS AS A RESULT OF THE NEW WORK. CONTRACTOR TO ALLOW FOR SCANNING THE CONCRETE PRIOR TO ANY CONDUIT PENETRATIONS TO ENSURE REBAR AND EMBEDDED SERVICES ARE MISSED.

JAPEGN Certificate of Authorization KGS Group No. 245

	FIELD BOOK #:				KGS				ENGINE
	POS	TED TO LBIS			GROUP Consulting Engineers				1
7					DESIGNED BY	DDW	CHECKED BY	JLL	
					DRAWN BY	GCN	APPROVED BY	RED	
	0	ISSUED FOR TENDER	2011-11-07 /9	l d	HDR. SCALE	N.T.S. N.T.S.	RELEASED FOR CONSTRUCTION		
	ND,	REVISIONS	1//	iy l	DATE	2011 09 19	DATE		



E05

THE CITY OF WINNIPEG WATER AND WASTE DEPARTMENT

REPLACEMENT OF RAW SEWAGE PUMP P-3 PERIMETER ROAD PUMPING STATION ELECTRICAL

LEVEL 200 PLAN

SHEET 1 OF 1CITY DRAWING NUMBER