


SECTION DETAIL KEYNOTES:

- 1) 10" SCH 80 PVC PIPE.
- 2) 8" DIA. ANSI 150 FLANGE LUG BODY HIGH PERFORMANCE BUTTERFLY VALVE BRAY SERIES 41 C/W 066 TRIM AND MANUAL GEAR OPERATOR.
- 3 8"x10" SCH 80 PVC REDUCER BUSHING AND PIPE AS REQUIRED.
- 4 10"x90° SCH 80 PVC ELBOW.
- 5 10" SCH 10S S/S SPOOL PIECE, LENGTH TO SUIT UV STRAINER BASKET, C/W ANSI 150 S/S FLANGES DRILL AND TAP FOR ITEM 8. PROVIDE FLANGES WITH FASTENERS AND GASKETS AS NOTED IN ITEM 7.
- 6 PIPING SUPPORT BY CONTRACTOR.
- 7) ANSI 150 FLANGES, PVC SIZE AS REQUIRED C/W TYPE 316 S/S FASTENER SETS. USE 1/8" THICK RING TYPE GASKETS, GARLOCK 3545.
- 8) 1/4" SCH 405 S/S PIPE NIPPLE C/W ISOLATION BALL VALVE AND COMPOUND PRESSURE GAUGE. DRILL AND TAP EDGE OF FLANGE FOR PRESSURE GAUGE.
- 9) EXTEND 4" HIGH CONCRETE HOUSEKEEPING PAD AS NOTED, 3'-0" WIDE.
- 10 8" SCH 80 PVC PIPE.

Certificate of Authorization


Accutech Engineering Inc.

No. 1660 Date: APR 10 2012





605-287 Broadway, Winnipeg, Manitoba Canada R3C 0R9 Phone 204.944.1555 Fax 204.944.1444 www.accutecheng.ca





CITY OF WINNIPEG
PAN AM POOL UV PIPING

SHEET TITL

MECHANICAL ROOM EAST NEW FLOOR PLAN AND SECTIONS

DRAWN BY	CHECKED BY	DATE	SHEET NO
VCV	BKW	APR 10 2012	M102
DESIGNED BY	CHECKED BY	SCALE	REVISION NO
BKW	KRD	AS NOTED	0