



**STANDARD LAYOUT**  
(REF. SD-229AA)

**NOTE:**

1. LINEUP DEPRESSED CURB WITH BACK OF SIDEWALK.
2. FOR SECTION A-A SEE SD-229C & SD-229D
3. INSTALL DETECTABLE WARNING SURFACE TILE IN ACCORDANCE WITH CW 3326, SECTION 3.1
4. REST AREA: REF. CW 3326, SECTION 3.2.1
5. IF L < 2300, CONSTRUCT MODIFIED BARRIER CURB 150 IN HEIGHT
6. CHANGES TO THE CONCRETE FINISH AREA AS DIRECTED BY THE CONTRACT ADMINISTRATOR

DIMENSIONS ARE IN MILLIMETRES



**THE CITY OF WINNIPEG**  
PUBLIC WORKS DEPARTMENT

Reference Spec. No.  
CW 3240, CW 3310, CW 3325, CW 3326

CURB RAMP FOR 1500  
SIDEWALK AT INTERSECTIONS

Designed By:  
B.P.

Drawn By:  
R.R.

Scale :  
N.T.S.

Checked By:  
B.P.

Date:  
12-12-15

Drawing No.

Approved:  
SURFACE WORKS REVIEW  
COMMITTEE

SD-229A