


NOTES:

- 1. PROVIDE MOUNTING RAIL TO MAXIMUM AVAILABLE LENGTH.
- REMOVE PORTIONS OF WIRE DUCT SIDEWALL TO ALLOW ENTRY OF FIELD CABLES FROM PANEL SIDES.

2 ENCLOSURE AND DEVICE FRONT PANEL SCALE: N.T.S.

1 ENCLOSURE AND DEVICE ARRANGEMENT SCALE: N.T.S.

	POS	POSTED TO LBIS			KGS GROUP CONSULTING ENGINEERS				EN	
E APEGIN						DESIGNED BY DRAWN	DDW	CHECKED BY	#	
ficate of Authorization						BY	GCN	APPROVED BY	#	
KGS Group						HOR. SCALE	N.T.S.	RELEASED FOR CONSTRUCTION		
No. 245	0	ISSUED FOR CONSTRUCT	ION	14/12/15	AP	VERTICAL	N.T.S.			
	NO.	REVISIONS		DATE	BY	DATE	2014 04 04	DATE		



D-E40.1

Winnipeg

THE CITY OF WINNIPEG WATER AND WASTE DEPARTMENT

FLOOD PUMPING STATION UPGRADES DUMOULIN STATION ELECTRICAL

RTU PANEL ENCLOSURE LAYOUT AND DETAILS

CITY DRAWING NUMBER 1-0139F-E0005-001