

x:\H-M\MORRISON HERSHFIELD LTD - 9164\13916401.01 - DETAILED DESIGN POLO PARK\CAD\CIVIL\PP DD PRODUCTION DRAWINGS\049-056 1391640100-DWG-C0014-A TO C0021-A ST JAMES.DWG 14.04.03 21:38

	234	.000												
	204	.000												
	222	.000												
	200	.000												
	232	.000												
	231	.000												
	201	.000												
7	230	.000												
	229	.000												
	228	.000												
-280														
MATCH LINE 1+280														
È														
1		N	OTES											
			ALL M EDITIO	ATERIA ON OF C	ITY OF	CONST WINNIP	RUCTIO	ON MET	HODS T	O COM	PLY WIT ON	TH LATE	ST	
			SPECI	FICATIO	лΝ.									

2. LOCATION OF ALL SEWER AND WATER MAINS AND SERVICES TO BE CONFIRMED IN FIELD PRIOR TO CONSTRUCTION. SEWER AND WATER SERVICES SHOWN ON DRAWINGS ARE APPROXIMATE ONLY. NOTIFY CONTRACT ADMINISTRATOR OF ANY DISCREPANCIES.

- 3. CONFIRM THAT SERVICES ARE ACTIVE BEFORE CONNECTING. ABANDON SERVICES NO LONGER IN USE WHERE DIRECTED BY THE CONTRACT ADMINISTRATOR. 4. CONDITION OF EXISTING SERVICES TO BE VERIFIED BY CONTRACT
- ADMINISTRATOR. NEWER OR GOOD CONDITION SERVICES TO REMAIN AND OLDER OR POOR CONDITION SERVICES TO BE RENEWED TO PROPERTY IINF
- 5. CONFIRM DEPTH OF SEWER SERVICES AT PROPERTY LINE USING SOFT DIG OR PIPE TRACING METHODS BEFORE ORDERING MAINLINE SEWER MANHOLES. CONTRACT ADMINISTRATOR MAY ADJUST MAINLINE SEWER DEPTH IF NECESSARY.
- 6. ALL SEWERS AND CATCHBASIN LEADS BENEATH PROPOSED PAVEMENT TO BE ABANDONED WITH FLOWABLE FILL TO SD-021. 7. INSTALL NEW SEWERS AND CATCHBASIN LEADS BY TRENCHLESS
- METHODS, UNLESS OTHERWISE NOTED. 8. CATCHBASIN OFFSETS ARE DIMENSIONED TO BACK OF CURB.
- 9. CATCHBASIN LEAD RISERS TO BE TYPE 'B' (SD-015). 10. ALL MANHOLES AND CATCHBASINS WITHIN SLIP-FORM PAVING AREAS TO INCLUDE 100mm RISER BELOW FRAME AND COVER. CATCHBASIN RISERS FOR SD-024 INSTALLATIONS WITH AP-008 FRAMES TO BE 2 X 50mm
- MODULOC TYPE PRECAST SQUARE RISERS. 11. ALL DEEP SHAFTS ON ST JAMES STREET, ST MATTHEWS AVENUE, AND ELLICE AVENUE TO HAVE CLASS 1 BACKFILL. SHALLOW EXCAVATIONS
- UNDER AND WITHIN 1.0m OF PAVEMENT OR SIDEWALK TO USE CLASS 3 BACKFILL. CLASS 5 BACKFILL TO BE USED UNDER BOULEVARD AREAS. 12. WATERMAIN TO HAVE 2.5m COVER FROM CENTRELINE OF ROAD. 100mm
- BOX INSULATION TO BE PROVIDED WHERE WATERMAINS AND SERVICES ARE SHALLOWER THAN 2.5m. 13. PUSH-ON WATERMAIN FITTINGS TO BE RESTRAINED AGAINST THRUST USING CONCRETE THRUST BLOCKS TO CITY OF WINNIPEG SD-004 AND SD-005. ADDITIONAL THRUST RESTRAINT USING JOINT HARNESSES WITH
- STAINLESS STEEL TIE RODS AND NUTS TO BE PROVIDED AS DIRECTED BY THE CONTRACT ADMINISTRATOR. 14. INSTALL WATERMAIN BY TRENCHLESS METHODS UNDER ALL PAVEMENTS, TREES AND OTHER APPURTENANCES.
- 15. ALL VALVES SHALL TURN COUNTER-CLOCKWISE TO CLOSE (RED
- OPERATING NUT). 16. INSTALL ALL HYDRANTS WITH FLANGE ELEVATION FROM 100mm TO 150mm
- ABOVE FINISHED GRADE. 17. SALVAGE ALL EXISTING HYDRANT ASSEMBLIES, VALVES AND VALVE BOXES AND RETURN TO CITY OF WINNIPEG PLINQUET YARD. REUSE EXISTING
- HYDRANTS ONLY AS DIRECTED. 18. CONTRACTOR TO NOTIFY BUSINESSES AND RESIDENTS A MINIMUM OF 48 HOURS PRIOR TO ANY DISRUPTION TO WATER SERVICE.
- 19. ADD 200.00m TO ABBREVIATED ELEVATIONS TO OBTAIN GEODETIC ELEVATIONS.

CHBASIN(LEAD AT 29 39	,						
74			cate of Authoriz				
		TETRA	A TECH WEI	Inc.			
SIN	SCALE 1:250	No. 5313	Date: April 3	30, 2014			
	5 0 5 10m	BID OPPOF	RTUNITY No.	210-2014			
A STATE	Winnipeg THE CITY OF Winnipeg PUBLIC WORKS ENGINEERIN	DEPA	RTMEN				
A THER	2013 POLO PARK	С	CITY DRAWING NUMBER D-13594				
	INFRASTRUCTURE IMPROVEMENT	S S	HEET OF 52	61			
/ING NO.	ST. JAMES STREET LAND DRAINAGE SEWER AND WATERM	AIN		REV			
	STA 1+150 TO STA 1+280		52	0			