

LEGEND							
SYMBOL	MBOL DESCRIPTION						
0 0	FLUORESCENT LIGHTING FIXTURE						
	EMERGENCY / EXIT LIGHT						
	REMOTE EMERGENCY LIGHTING DOUBLE HEAD						
\$	SINGLE POLE 15A SWITCH						
\$ _{тs}	TIMER SWITCH						
\ominus	RECEPTACLE						
ос	OVER THE COUNTER						
BC	BELOW COUNTER						
	COMBINATION DATA PORT						
SRD	SCALE REMOTE DISPLAY						
SD	SCALE DIGITIZER						
PIRD	PASSIVE IR DETECTOR						
ND	NOTIFICATION DEVICE						
KPA	KEY PAD ALARM						
GB	GLASS BREAKAGE						
DC	DOOR CONTACTS						
PA	CLERK PANIC ALARM BUTTON						
Ŗ	OUTDOOR LIGHT						
	SECURITY CAMERA						

NOTE:

1. PROVIDE RELAY CONTROL PANEL TO ACTIVATE EMERGENCY FIXTURES ON. FAILING OF LIGHTING CIRCUIT FOR THE AREA SERVED.

SCALE HOUSE - LIGHTING PLAN 1:25

PANEL TO ACTIVATE EMERGENCY	
LIGHTING CIRCUIT FOR THE AREA	

			LIGHTI						
TYPE			DESCRIPTION		MANUFACTUR	MANUFACTURER			
A	STE COL HIG	RT5SX - 28W, 2-LAMP, FLUORESCENT FIXTURE, ENERGY EFFICIENT, RUGGED, STEEL REFLECTOR WITH EMBOSSED FACETS, HOUSING FORMED FROM COLD-ROLLED STEEL, REGRESSED, TWO-PIECE REFRACTIVE SYSTEM, C/W HIGHLY EFFICIENT PROGRAM-START ELECTRONIC BALLAST, CLASS P, THERMALLY PROTECTED.			LPM835P	CAT. No. 2RT5SX-28T5-MVOLT-GEB95-			
В	ALL	21W LED OUTDOOR LED FLOOD SERIES, 120V LIGHTING FIXTURE, DIE CAST ALUMINUM CONSTRUCTION, POWDER COAT BRONZE FINISH, WALL MOUNT ABOVE DOOR.			COOPER LIGHTING ALL PRO CAT. No. F-S-S1530L-PC-ES OR APPROVED EQUAL		Certificate of Authorization Dillon Consulting Limited (MB) No. 1789 Date:2014/06/19 METRIC WHOLE NUMBERS INDICATE MILLIMETRES DECIMALIZED NUMBERS INDICATE METRES		
C	RT5N - NARROW RECESSED, 28W, 1-LAMP, FLUORESCENT FIXTURE, ENERGY EFFICIENT, RIGID COLD-ROLLED STEEL HOUSING, C/W HIGHLY EFFICIENT PROGRMM-START ELECTRONIC BALLAST, CLASS P, THERMALLY PROTECTED.			LITHONIA LIGHTING CAT. No. RT5N-1-28T5-MVOLT-GEB95- LPM835P OR APPROVED EQUAL		28W T5 (46")			
EMERG LIGHT	EMERG. LIGHTEMERGENCY LIGHT FIXTURE WITH 2 LED HEADS, WHITE ENCLOSURE, WITH 120V INPUT LINE CORD.			COOPER CAT. No. RCS-1-8-2-LED-2 OR APPROVED EQUAL					
			DESIGNED BY JAD DRAWN BY MS CHECKED		NGINEER'S SEAL	Winnip		HE CITY OF W WATER AND WASTE	
			APPROVED BY ARR	DILLON CONSULTING	APOFESSIONAL	BRADY R		NNIPEG DEPOTCITY DRAWING NUMBERROAD RESOURCE1-0400A-E0003-00SHEETOF28	
	14/06/19 DATE	ARR BY	HOR. SCALE 1:25 VERTICAL DATE MARCH 2014	RELEASED FOR CONSTRUCTION DATE	CONSULTANT PROJECT NUMBER	SCA	LE HO	USE LIGHTING PLAN	consultant drawing number E3

	TYPE DESCRIPTION				RER	LAMP				
			STEEL REF COLD-ROLL HIGHLY EF	W, 2-LAMP, FLUORESCENT FIXT LECTOR WITH EMBOSSED FAC LED STEEL, REGRESSED, TWO- FICIENT PROGRAM-START ELEO Y PROTECTED.	CAT. No. 2RT5SX-28T5-MVOLT-0 LPM835P	CAT. No. 2RT5SX-28T5-MVOLT-GEB95-				
	E			UTDOOR LED FLOOD SERIES, CONSTRUCTION, POWDER CO OR.	CAT. No. F-S-S1530L-PC-ES					
		C RT5N - NARROW RECESSED, 28W, 1-LAMP, FLUORESCENT FIXTURE, ENERGY EFFICIENT, RIGID COLD-ROLLED STEEL HOUSING, C/W HIGHLY EFFICIENT PROGRMM-START ELECTRONIC BALLAST, CLASS P, THERMALLY PROTECTED. LITHONIA LIGHTING CAT. No. RT5N-1-28T5-MVOLT-GEB95- LPM835P OR APPROVED EQUAL 28W T5 (46")		Certificate of Authorization Dillon Consulting Limited (MB) No. 1789 Date: <u>2014/06/19</u>						
				CY LIGHT FIXTURE WITH 2 LED T LINE CORD.	HEADS, WHITE ENCLOSURE, WITH	COOPER CAT. No. RCS-1-8-2-LED-2 OR APPROVED EQUAL			WHOLE NUMBE	IETRIC RS INDICATE MILLIMETRES UMBERS INDICATE METRES
B.M. ELEV.				DESIGNED BY JAD DRAWN BY MS CHECKED		ENGINEER'S SEAL	Winnip		HE CITY OF V WATER AND WASTE	
				BY BM APPROVED BY ARR	DILLON CONSULTING	MOORE 2014/06/19		BRADY F	NNIPEG DEPOTCity drawing numberROAD RESOURCE1-0400A-E0003-001SHEETOF2835	
	ISSUED FOR TENDER	14/0	6/19 ARR	HOR. SCALE 1:25 VERTICAL DATE MARCH 2014	RELEASED FOR CONSTRUCTION	CONSULTANT PROJECT NUMBER	SCA	ALE HOU	JSE LIGHTING PLAN	consultant drawing number E3

<u>O</u>	4	0
0		
<		
0		