


## NOTES:

- 1. USE DIAGRAM AS GUIDELINE ONLY.
- THE BOTTOM OF THE TRENCH & THE BACKFILL MATERIAL IS ROCK FREE. 2.
- 3. SAND BEDDING IS IN PLACE.
- 4. ENSURE PROPER COMPACTION OF EXCAVATED AREAS.
- ENSURE PROPER LOCATION, PLACEMENT, & DEPTH OF CABLE 5.
- 6. ENSURE PROPER PLACEMENT OF MARKER TAPE ALONG CABLE PER CODE.
- 7. ENSURE PADS, BOXES, & BASES INSTALLED TO PROPER LEVEL & GRADE ACCORDING TO DESIGNS & PLANS.
- BACKFILL SHALL BE ONLY DONE AFTER INSPECTOR APPROVED THE CABLE INSTALLATION. 8.
- 9. CABLES FROM METER & TO METER TO BE INSIDE WALL CAVITY.



204 488 3857 tel. 204 488 0216 fax. www.bridgmancollaborative.ca hridoman collaborative SHED

678 MAIN STREET WINNIPEG, MB R3B 1E4

490 KEENLEYSIDE EAST ELMWOOD STORAGE

Bid Opportunity	Drawing Title:	ISSUE
Number:	ELECTRICAL SYSTEMS -	
630-2016	SINGLE LINE DIAGRAM	Date

## NOTES

1 CIRCUIT BREAKER PROTECTION: 1. FULLY RATED OR USING SERIES RATED COMBINATIONS

2. INTEGRATED EQUIPMENT RATED (IER) WHEN USING SERIES-RATED SYSTEMS, THEY SHALL

USING SERIES-RATED STATEMS, THE T SHALL BE TESTED/LABELED AS A SERIES-RATED COMBINATION 3. LABEL/NAMEPLATE TO BE INSTALLED IN A CONSPICUS AND LEGIBLE MANNER TO INDICATE THAT THEY SHOULD ONLY BE REPLACED WITH COMPONENTS OF THE SAME TYPE AND RATING REFER TO CEC 14-014

2 DOWNSTREAM OVERCURRENT DEVICES MUST BE SERIES RATED COMBINATIONS WITH THE UPSTREAM PROTECTIVE DEVICE. FOR SERIES

UPSTREAM PROTECTIVE DEVICE. FOR SERIES RATED COMBINATIONS, EACH DEVICE MUST BE LABELED TO INDICATE: 1. THAT REPLACEMENT COMPONENTS MUST BE 0F THE SAME TYPE AND RATING ONLY 2. TESTED IER KA RATING 3. SPECIFIC UPSTREAM PROTECTIVE DEVICE 4. PERMISSIBLE BRANCH DEVICES 5. PANELBOARD DESIGNATION 6. VOLTAGE


3 SERVICE ENTRANCE EQUIPMENT TO MEET UTILITY REQUIREMENTS

4 SUPPLY & INSTALL PANELS MAKE: EATON, PANEL CIRCUITING AS PER SCHEDULE, PANEL TO BE SUITABLE FOR WET ENVIRONMENT.

<sup>5</sup> SUPPLY & INSTALL GROUND BONDING WIRE SIZE #6 AWG-CU- STRANDED BACK TO MAIN BUILDING GROUND BONDING CONDUCTOR.

6 SUPPLY & INSTALL BREAKER IN CDP TO BE 100AMPS C/W INTERRUPTING RATING AS NOTED. SUPPLY & INSTALL IDENTIFICATION LABEL TO MATCH EXISTING.

7 SUPPLY & INSTALL SPLITTER BOX FOR 100A 120/208V 3PH - 4 WRE AS NOTED ON DRAWINGS. SUPPLY & INSTALL PERMANENT ATTACHED LAMACOID LABEL TO IDENTIFY UNIT, SUPPLY & LOAD CIRCUITS.



cannot be reproduced or used without the consent of the Architect. The contractor is

responsible for checking and verifying all levels and dimensions and shall report all

discrepancies to the Architect and obtain clarification prior to commencing work.

ED FOR CONSTRUCTION

Sheet No:

E03

e: JULY 29, 2016