

		ITEM SUMMARY FOR ALL EQUIPMENT	
TEM	QUANTITY	DESCRIPTION	FINISH
1	3	75 L/S NON-CLOG PUMP CORNELL 20HP MODEL 68HTA-VF16	C.I.
2	7	200mm METAL SEATED GATE VALVE	D.I.
3	3	200mm RUBBER FLAPPER CHECK VALVE	D.I.
4	3	150mm x 200mm ECCENTRIC REDUCER	D.I.
5	4	200mm 90° ELBOW	D.I.
6	2	200mm 45° ELBOW	D.I.
7	1	200mm 45° LATERAL WYE	D.I.
8	3	PUMP DRIVE SHAFT	C.S.
9	3	VERTICAL MOUNTED MOTOR	
10	2	200mm FLOW METER	
11	1	200mm STANDARD PIPE	D.I.
12	1	MODIFIED DISPLACED PRESSURE TRANSMITTER	
13	1	NEW DISPLACED PRESSURE TRANSMITTER	
14	1	200mm TEE	D.I.
15	3	200mm SUCTION PIPE	D.I.
16	8	PIPE SUPPORT	C.I.
17	3	PUMP BASE	C.I.
18	3	SHAFT BEARING ASSEMBLY	C.I.
19	3	NEW CONCRETE PAD	
20	6	50mm BALL VALVE	PVC
21	1	50mm FLUSH OUT VALVE	PVC
22	1	50mm CLEAR SIGHT GLASS PIPE	PVC
23	1	50mm STANDARD PVC PIPE	PVC
24	6	50mm PVC TEE	PVC
25	2	50mm CHECK VALVE	PVC
26	1	PRESSURE GAUGE	
27	4	CEILING MOUNTED PIPE SUPPORT	





- NOTE:

- 5. PROVIDE APPROPRIATE SPACER FOR ANY MINUTE GAPS BETWEEN FITTINGS
- 7. IN SECTION B, PUMP P-L02, AND MOTOR AND SHAFT FOR PUMP P-L01 ARE IS NOT