

NOTES:

- 1. BACKBOARD THICKNESS SHALL BE 0.135 INCH +0.02/-0.00INCH
- 2. EACH BACKBOARD SHALL BE FROM A SINGLE PIECE OF OPAQUE, NOT TRANSPARENT FLAT POLYCARBONATE SHEET STOCK.
- 3. PLUMBIZED BACKBOARDS SHALL BE CONTINUOUSLY ADJUSTABLE SO AS TO FIT PLUMBIZER BRACKETS RANGING FROM ONE (1") INCH THICK TO TWO (2") INCHES THICK (THICKNESS BEING DEFINED AS THE SEPARATION DISTANCE REQUIRED BETWEEN THE TWO (2) HEAD SECTIONS TO ACCOMMODATE THE PLUMBIZER). TO PROVIDE THIS ADJUSTABILITY, BACKBOARDS SHALL HAVE A DETACHABLE TAB ABOVE THE TOP SECTION AND BETWEEN THE TOP AND MIDDLE SECTIONS.

IMPERIAL

ALL DIMENSIONS SHOWN ON THIS PLAN ARE IN INCHES UNLESS OTHERWISE INDICATED

DESIGNED BY S.D. Nov 09/15
CHECKED BY ______
APPROVED BY _____
DATE

POLYCARBONATE BACKBOARD



THE CITY OF WINNIPEG

PUBLIC WORKS DEPARTMENT TRANSPORTATION DIVISION TRAFFIC SIGNALS BRANCH SCALE N.T.S.

DRAWING NO.

BB-1